

Mark Scheme (Results)

Summer 2017

Pearson Edexcel International GCSE

Physics (4PH0) Paper 1P

Science (Double Award) (4SC0) Paper 1P

Pearson Edexcel Level 1/Level 2 Certificate

Physics (KPH0) Paper 1P

Science (Double Award) (KSC0) Paper 1P

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk. Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Question number	Answer	Notes	Marks
1 (a)	<p>D; (beta particle)</p> <p>The only correct answer is D</p> <p>A is not correct because it is an em wave</p> <p>B is not correct because it is an em wave</p> <p>C is not correct because it is a particle with 2p and 2n</p>		1
(b) i	<p>A; (a nucleus)</p> <p>The only correct answer is A</p> <p>B is not correct because electrons are negative and thus attract the positive nucleus</p> <p>C is not correct because gamma rays are uncharged</p> <p>D is not correct because neutrons are uncharged</p>		1
ii	<p>C;</p> <p>The only correct answer is C</p> <p>A is not correct because it shows no deflection and alpha particles should be repelled</p> <p>B is not correct because it shows attraction</p> <p>D is not correct because it shows attraction</p>		1
iii	<p>D;</p> <p>The only correct answer is D</p> <p>A is not correct because it penetrates bone whereas alpha particles would be stopped by skin</p> <p>B is not correct because it penetrates muscle</p> <p>C is not correct because it penetrates skin</p>		1

iv	<p>A;(high ionising ability)</p> <p>The only correct answer is A</p> <p>B is not correct because mass of radioactive source or particle is irrelevant to smoke detectors</p> <p>C is not correct because the half-life does not affect how a smoke detector works, but how long it works for</p> <p>D is not correct because alpha particles have a short range</p>		1

Total for question 1 = 5 marks

Question number	Answer	Notes	Marks
2 (a)	Metals conduct heat; Suitable qualifier DOP; e.g. quickly/good/better than non-metals	condone 'metals conduct' for 1 mark	2
(b)	Black; (because) they are good emitters;	ignore references to absorption, radiation	2
c i	Any four from:- MP1. air next to radiator; MP2. air (particles) gains thermal energy /particles move faster; MP3. spaces between particles increase; MP4. this heated air is less dense; MP5. (therefore) hot air rises;	allow air becomes hot allow air particles are more spread out, air expands but not air particles expand ignore hot air particles are less dense ignore heat rises	4
c ii	any sensible suggestion; e.g. maximise surface area	allow lots of smaller pipes increase temperature of hot water radiator lower down	1

Total for question 2 = 9 marks

Question number	Answer	Notes	Marks
3 a	ultraviolet;	UV	1
b	gamma;	accept γ	1
c	frequency decreases; because $c = f \cdot \lambda$ OR speed is constant;	accept eqn in words all travel at same speed	2
d	infrared;	IR	1
e i	any three from:- MP1. time taken (is noted); MP2. for the beam /microwaves to get to plane and return; MP3. distance calculated from speed = distance/time; MP4. distance is halved;	for signal to get to plane and back accept 'bounce back' any form of the eqn allow time halved	3
ii	any suitable and sensible suggestion; e.g. <ul style="list-style-type: none"> • planes move very fast • planes travel a long distance in a short time • planes can arrive from any direction • updates distance/position of plane frequently 		1

Total for question 3 = 9 marks

Question number	Answer	Notes	Marks
4 a (i)	covered with a non-conductor/eq;	accept named insulator e.g. plastic, rubber do not accept thermal ideas	1
(ii)	Any two from MP1. a (thin) wire which melts /eq; MP2. when current in excess of 5A/which limits the current to 5A; MP3. to break the circuit;	low melting point, 'blows' allow at 5A allow 'stops the current' 'cuts off the current'	2
(iii)	outside case is made of metal/eq; direct connection to ground;	allow conducting for metal e.g. 'connected to earth' 'connected to the earth (pin) in the plug'	2
(iv)	outside case (of appliance) is made of an insulator / there is no metal or conductor on the outside; (therefore) can't get a shock from it/it doesn't need to be earthed/it is safe to touch;	ignore wires, leads accept named insulator no need for earth lead	2
(b)	re-settable; cuts off the circuit faster;	allow reusable detects leakage current in the earth lead ignore cost	2

Total for question 4 = 9 marks

Question number	Answer	Notes	Marks
5 a	<p>any four from:-</p> <p>MP1. nuclear to KE (of fission products);</p> <p>MP2. KE (of fission products) to thermal energy (of coolant);</p> <p>MP3. thermal energy (of coolant) to thermal energy (of water);</p> <p>MP4. thermal energy (of water) transferred to KE of the steam;</p> <p>MP5. KE of steam transferred to KE of turbines;</p> <p>MP6. KE of turbines transferred to electrical energy in generator;</p>	<p>allow nuclear to thermal for 1 mark instead of MP1 AND MP2</p> <p>allow thermal energy to KE for 1 mark instead of MP3 AND MP4</p> <p>allow KE to electrical energy for 1 mark instead of MP5 AND MP6</p>	4
b	<p>C; (hydroelectric power station)</p> <p>The only correct answer is C</p> <p>A is not correct because wind farms use KE</p> <p>B is not correct because geothermal power stations use thermal energy</p> <p>D is not correct because coal-fired power stations use thermal energy</p>		1
c	<p>A; (coal-fired power station)</p> <p>The only correct answer is A</p> <p>B is not correct because solar farms use em radiation</p>		1

		<p>C is not correct because hydroelectric power stations use GPE</p> <p>D is not correct because wind farms use KE</p>		
d	i	<p>B; (thermal)</p> <p>The only correct answer is B</p> <p>A is not correct because lamps do not emit sound in normal use</p> <p>C is not correct because electrical energy is the input energy</p> <p>D is not correct because light is the useful energy output</p>		1
	ii	<p>efficiency = $\frac{\text{useful (energy) output}}{\text{total (energy) input}}$;</p>	with or without 'x100'	1
	iii	<p>substitution; evaluation; e.g. Efficiency = $\frac{1.5}{188}$ (X100) = 0.0080 (0.80 as a %)</p>	<p>0.007979 or 0.7979 %</p> <p>0.008% loses 1 mark</p>	2

Total for question 5 = 10 marks

Question number	Answer	Notes	Marks																																												
6 a i	any one of:- background light affects readings (of LDR); to control the level of light;	light affects results / LDR idea of fair test	1																																												
	ii <table border="1" data-bbox="277 331 1359 608"> <thead> <tr> <th data-bbox="277 331 639 395">type of variable</th> <th data-bbox="639 331 951 395">example</th> <th data-bbox="951 331 1359 395">accept</th> </tr> </thead> <tbody> <tr> <td data-bbox="277 395 639 487">control</td> <td data-bbox="639 395 951 487">light level in the room/eq;</td> <td data-bbox="951 395 1359 487">voltage / power of source</td> </tr> <tr> <td data-bbox="277 487 639 544">dependent</td> <td data-bbox="639 487 951 544">current;</td> <td data-bbox="951 487 1359 544"></td> </tr> <tr> <td data-bbox="277 544 639 608">independent</td> <td data-bbox="639 544 951 608">light intensity;</td> <td data-bbox="951 544 1359 608">distance from LDR;</td> </tr> </tbody> </table>	type of variable	example	accept	control	light level in the room/eq;	voltage / power of source	dependent	current;		independent	light intensity;	distance from LDR;		3																																
type of variable	example	accept																																													
control	light level in the room/eq;	voltage / power of source																																													
dependent	current;																																														
independent	light intensity;	distance from LDR;																																													
b i	<table border="1" data-bbox="319 710 989 783"> <tr> <td data-bbox="319 710 536 783">50</td> <td data-bbox="536 710 639 783">3.9</td> <td data-bbox="639 710 743 783">16.0</td> <td data-bbox="743 710 847 783">3.8</td> <td data-bbox="847 710 989 783">7.9</td> </tr> </table>	50	3.9	16.0	3.8	7.9	allow ans which round to 3.9 e.g. 3.85 allow truncation e.g. 3.8	1																																							
	50	3.9	16.0	3.8	7.9																																										
ii 3.9 (mA);																																															
c i	labels (quantity and unit) on both axes; scales on both axes; points (to ½ sq); <table border="1" data-bbox="277 1247 794 1613"> <thead> <tr> <th data-bbox="277 1247 411 1342" rowspan="2">Distance from lamp in cm</th> <th colspan="4" data-bbox="411 1247 794 1278">Current in mA</th> </tr> <tr> <th data-bbox="411 1278 507 1342">1st reading</th> <th data-bbox="507 1278 595 1342">2nd reading</th> <th data-bbox="595 1278 683 1342">3rd reading</th> <th data-bbox="683 1278 794 1342">Average (mean)</th> </tr> </thead> <tbody> <tr> <td data-bbox="277 1342 411 1385">10</td> <td data-bbox="411 1342 507 1385">100.1</td> <td data-bbox="507 1342 595 1385">102.8</td> <td data-bbox="595 1342 683 1385">109.6</td> <td data-bbox="683 1342 794 1385">104.2</td> </tr> <tr> <td data-bbox="277 1385 411 1427">20</td> <td data-bbox="411 1385 507 1427">26.9</td> <td data-bbox="507 1385 595 1427">25.1</td> <td data-bbox="595 1385 683 1427">25.8</td> <td data-bbox="683 1385 794 1427">25.9</td> </tr> <tr> <td data-bbox="277 1427 411 1470">30</td> <td data-bbox="411 1427 507 1470">10.6</td> <td data-bbox="507 1427 595 1470">10.7</td> <td data-bbox="595 1427 683 1470">11.7</td> <td data-bbox="683 1427 794 1470">11.0</td> </tr> <tr> <td data-bbox="277 1470 411 1513">40</td> <td data-bbox="411 1470 507 1513">6.1</td> <td data-bbox="507 1470 595 1513">6.2</td> <td data-bbox="595 1470 683 1513">5.8</td> <td data-bbox="683 1470 794 1513">6.0</td> </tr> <tr> <td data-bbox="277 1513 411 1555">50</td> <td data-bbox="411 1513 507 1555">3.9</td> <td data-bbox="507 1513 595 1555">16.0</td> <td data-bbox="595 1513 683 1555">3.8</td> <td data-bbox="683 1513 794 1555">7.9</td> </tr> <tr> <td data-bbox="277 1555 411 1598">60</td> <td data-bbox="411 1555 507 1598">2.9</td> <td data-bbox="507 1555 595 1598">2.7</td> <td data-bbox="595 1555 683 1598">2.9</td> <td data-bbox="683 1555 794 1598">2.8</td> </tr> <tr> <td data-bbox="277 1598 411 1640">80</td> <td data-bbox="411 1598 507 1640">1.6</td> <td data-bbox="507 1598 595 1640">1.5</td> <td data-bbox="595 1598 683 1640">1.5</td> <td data-bbox="683 1598 794 1640">1.5</td> </tr> </tbody> </table>	Distance from lamp in cm	Current in mA				1st reading	2nd reading	3rd reading	Average (mean)	10	100.1	102.8	109.6	104.2	20	26.9	25.1	25.8	25.9	30	10.6	10.7	11.7	11.0	40	6.1	6.2	5.8	6.0	50	3.9	16.0	3.8	7.9	60	2.9	2.7	2.9	2.8	80	1.6	1.5	1.5	1.5	check that scale is linear and occupies at least half the grid -1 for each error accept point (50, 3.9) or (50, 7.9)	4
	Distance from lamp in cm		Current in mA																																												
1st reading		2nd reading	3rd reading	Average (mean)																																											
10	100.1	102.8	109.6	104.2																																											
20	26.9	25.1	25.8	25.9																																											
30	10.6	10.7	11.7	11.0																																											
40	6.1	6.2	5.8	6.0																																											
50	3.9	16.0	3.8	7.9																																											
60	2.9	2.7	2.9	2.8																																											
80	1.6	1.5	1.5	1.5																																											
c ii	curve of best fit;	if point (50,7.9) plotted line must avoid this point	1																																												

d	i	<p>pattern sentence; e.g. as distance increases, current decreases</p> <p>it's a non-linear relationship;</p>	<p>allow</p> <ul style="list-style-type: none"> • decreasing rate • curved line (of best fit) • slope changes • inverse square <p>reject</p> <ul style="list-style-type: none"> • negative correlation • inversely proportional • exponential 	2
d	ii	resistance reduces;	however expressed	1
e		<p>shifted downwards;</p> <p>(because) less light gets through;</p>	accept shifted to LEFT (assumes inverse graph plotted)	2

Total for question 6 = 16 marks

Question number	Answer	Notes	Marks
7 a i	drag/friction labelled on up arrow; weight labelled on down arrow; both arrows same size;	ignore upthrust, resultant, unqualified resistance, air resistance reject unqualified gravity judge by eye	3
	ii force up = force down; (therefore) no acceleration; (hence $TV =$) constant velocity/speed;	accept <ul style="list-style-type: none"> • weight = drag (or resistance or friction) • balanced forces • resultant force is zero ignore maximum velocity	3
b i	any two from:- long thin container e.g. measuring cylinder; metre rule; (electric) balance; micrometer; light gates; stop clock/ EQ; magnet (to remove the balls);	ignore oil, steel balls, condone beaker allow ruler, (metal) tape measure scales callipers	2
	ii any 5 from:- MP1. labelled diagram; MP2. fixed and measured distance; MP3. time over the distance; MP4. measures diameter or mass; MP5. repeat and average (for same ball); MP6. use of speed = distance/ time; MP7. prelim experiment to determine range / criterion for choice of range; MP8. start some distance from the top/allow for forces to equalise; MP9. determine velocity at different points and plot graph;	the medium can be air, water or oil must be more than repeat of previous diagram mark start and end position allow repeat for reliability criterion for diameter of ball	5

c	discussion of either idea of discrete data (however expressed); bar chart DOP; or data is continuous (however expressed); scatter gram DOP;	Allow line graph	2
---	---	------------------	---

Total for 7 = 15 marks

Question number	Answer	Notes	Marks
8 a	to reduce drag/eq;	aerodynamic, streamlined	1
b i	work done = force X distance (moved in direction of force);	in words or accepted symbols	1
	ii	conversion of units; substitution; evaluation; e.g. 180 000 x 17 3 100 000 (J)	3
	iii	substitution; evaluation; unit; e.g. $\frac{3\ 060\ 000}{8}$ 380 000 W	3
c i	acceleration = $\frac{\text{change of velocity}}{\text{time taken}}$	in words or accepted symbols e.g. $\Delta v/t$	1
	ii	substitution; evaluation; e.g. $= \frac{14.8 - 6}{6} = \frac{8.8}{6}$ $= 1.5 \text{ (m/s}^2\text{)}$	2
	iii	distance = area under graph; one area correct; correct answer; e.g. $\frac{1}{2} \times 6 \times 8.8$ or 6×6 or 14.8×2 92 (m)	3
		seen or implied	
		1.467 ans in range 1.4 to 1.5	
		6 x 8 or 2 x 8.8	
		ans which round to 92	

d	i	$P = F/A;$	in words or accepted symbols or rearranged	1
	ii	<p>factor of 6 (wheels) accounted for; substitution; rearrangement; evaluation; e.g. $240\ 000 = 180\ 000/A$ $A = \frac{180\ 000}{240\ 000}$ $= 0.75\ \text{m}^2$ for 6 $0.13\ (\text{m}^2)$</p>	<p>$0.125\ (\text{m}^2)$</p> <p>if 0.75 seen, then 3 marks</p> <p>POT errors = -1 CHECK carefully as $240000/180000 = 1.33$</p>	4

Total for question 8 = 19 marks

Question number	Answer	Notes	Marks
9 a i	idea that ray does not change direction at A;	allow so it can calculate angle at B condone no refraction	1
ii	idea that refraction is wavelength/colour dependent;	allow • dispersion for refraction, • would get different angles/spectrum for different colours	1
iii	the normal;		1
b i	$61^\circ \pm 2^\circ$		1
ii	$\frac{\sin i}{\sin r} = n$	allow sine	1
iii	substitution; evaluation (to 2 SF); e.g. $\frac{\sin 61}{\sin 30} = n_{\text{air to glass}}$ $n_{\text{air to glass}} = 1.7(49)$	allow ecf from (b) (i) allow evaluation to 3 or 4 SF $\frac{\sin 30}{\sin 61} = n_{\text{glass to air}}$ $n_{\text{glass to air}} = 0.57(0.572)$ accept ans in range 1.7 to 1.8 (0.56 to 0.58)	2
c i	$\sin c = 1/n$; OR either of these for both marks c is the angle (of incidence) inside the glass above which TIR occurs;; c is the angle (of incidence) inside the glass for which refracted angle is 90° ;;	allow a labelled diagram	2
ii	reflection shown; at the correct angle;	judge by eye reflection plus refraction = 0	2

Total for question 9 = 11 marks

Question number	Answer	Notes	Marks
10 a i	a nucleus splits ;	not atom	1
ii	using a conservation of nucleons method; 2;		2
iii	MP1. one of the released neutrons is absorbed by another uranium nucleus ;	allow hits, collides allow matching plurals	2
	MP2. (hence) releasing more or other neutrons;	ignore creates neutron	
iv	MP1. barium or krypton named;	allow symbols	2
	MP2. (one of the two nuclei) formed from (uranium) fission / splitting;	ignore emission/come off etc care that repeat of stem is not credited	
b	MP1. a neutron changes into proton;	$1n \rightarrow 1p + 1e$	2
	MP2. mass/nucleon number remains constant;	allow 'it' ignore 'electrons have no mass'	

Total for question 10 = 9 marks

Question number	Answer	Notes	Marks
11 a	any two of:- MP1. pull (existing) magnet out of coil; MP2. push S pole first into coil; MP3. push N pole into other side of coil; MP4. reverse the connections to the coil;	magnet moves to L etc reverse the magnet	2
b i	coil moves through /cuts; the magnetic field (of the magnet);	conductor or wire moving through allow rotates through magnetic field lines	2
ii	any two from:- MP1. faster rotation; MP2. stronger magnet or field; MP3. more turns on the coil; MP4. larger area of coil;	(soft) iron core more coils on the loop	2
iii	any two from:- MP1. energy is transferred to/by lamp; MP2. more input energy required; MP3. so more work done (moving coil);	energy is lost as thermal energy or light in the lamp coil works harder	2

Total for question 11 = 8 marks

Total = 120

